



# United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
09/904,077	07/12/2001	Jan Willem Aarts	NL 000403	1891	
24737	7590 05/12/2005		EXAM	EXAMINER	
PHILIPS INTELLECTUAL PROPERTY & STANDARDS P.O. BOX 3001			AGUSTIN, PET	AGUSTIN, PETER VINCENT	
	BRIARCLIFF MANOR, NY 10510			PAPER NUMBER	
			2652		

DATE MAILED: 05/12/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

	A II 4I NI	A 11-4/			
	Application No.	Applicant(s)			
Office Action Summan	09/904,077	AARTS ET AL.			
Office Action Summary	Examiner	Art Unit			
The MANUALO DATE of this	Peter Vincent Agustin	2652			
The MAILING DATE of this communication app Period for Reply	pears on the cover sheet with the c	orrespondence address			
A SHORTENED STATUTORY PERIOD FOR REPLY THE MAILING DATE OF THIS COMMUNICATION.  - Extensions of time may be available under the provisions of 37 CFR 1.1 after SIX (6) MONTHS from the mailing date of this communication.  - If the period for reply specified above is less than thirty (30) days, a reply If NO period for reply is specified above, the maximum statutory period of Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	36(a). In no event, however, may a reply be time within the statutory minimum of thirty (30) days will apply and will expire SIX (6) MONTHS from a cause the application to become ABANDONE	nely filed s will be considered timely. the mailing date of this communication. O (35 U.S.C. § 133).			
Status					
2a) ☐ This action is <b>FINAL</b> . 2b) ☐ This 3) ☐ Since this application is in condition for alloward	☐ This action is FINAL. 2b)☐ This action is non-final.				
Disposition of Claims					
4) ☐ Claim(s) 1-20 is/are pending in the application. 4a) Of the above claim(s) is/are withdrawn from consideration.  5) ☐ Claim(s) is/are allowed.  6) ☐ Claim(s) 1-20 is/are rejected.  7) ☐ Claim(s) is/are objected to.  8) ☐ Claim(s) are subject to restriction and/or election requirement.					
Application Papers					
9) ☐ The specification is objected to by the Examine 10) ☑ The drawing(s) filed on 04 March 2005 is/are:  Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct 11) ☐ The oath or declaration is objected to by the Example 11.	a)⊠ accepted or b)⊡ objected to drawing(s) be held in abeyance. See ion is required if the drawing(s) is obj	e 37 CFR 1.85(a). ected to. See 37 CFR 1.121(d).			
Priority under 35 U.S.C. § 119					
<ul> <li>12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).</li> <li>a) All b) Some * c) None of:</li> <li>1. Certified copies of the priority documents have been received.</li> <li>2. Certified copies of the priority documents have been received in Application No.</li> <li>3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).</li> <li>* See the attached detailed Office action for a list of the certified copies not received.</li> </ul>					
Attachment(s)					
1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date	Paper No(s)/Mail Da	Paper No(s)/Mail Date  5) Notice of Informal Patent Application (PTO-152)			

Application/Control Number: 09/904,077 Page 2

Art Unit: 2652

#### **DETAILED ACTION**

### Drawings

1. Replacement drawings were received on March 4, 2005. These drawings are acceptable.

## Claim Objections

- 2. Claims 8 & 15 are objected to under 37 CFR 1.75(c), as being of improper dependent form for failing to further limit the subject matter of a previous claim. Applicant is required to cancel the claim(s), or amend the claim(s) to place the claim(s) in proper dependent form, or rewrite the claim(s) in independent form. See also MPEP 608.01(n), "Infringement Test" for dependent claims.
- 3. Claims 16-18 & 20 are objected to because of the following informalities:

Claim 16, line 17: "parallel the" should be --parallel to the--.

Claim 17, line 1: "as in" should be --as claimed in--.

Claim 17, line 1: "pairs of portions" should be --pair of portions--.

Claim 17, line 2: "contain" should be --contains--.

Claim 18, line 1: "as in" should be --as claimed in--.

Claim 18, line 1: "pairs of portions" should be --pair of portions--.

Claim 18, line 2: "contain" should be --contains--.

Claim 20, line 1: "previously presented" should be --new--.

Appropriate correction is required.

## Claim Rejections - 35 USC § 102

4. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- 5. Claims 1-20 are rejected under 35 U.S.C. 102(b) as being anticipated by Schell et al. (US 6,058,081).

In regard to claim 1, Schell et al. disclose an optical scanning device (Figure 26) for scanning an information layer of an optically scannable information carrier, which scanning device is provided with a radiation source, an optical lens system (2-12) with an optical axis for focusing a radiation beam supplied, in operation, by the radiation source into a scanning spot on the information layer, and an actuator (Figure 26) by means of which the lens system can be displaced with respect to a stationary part of the scanning device at least in a direction parallel to the optical axis, the actuator being provided with an electric coil system (2-16, 2-18 & 2-20). which is arranged in a fixed position with respect to the lens system, and a magnetic system (2-22 & 2-24) which is arranged in a fixed position with respect to the stationary part, characterized in that the magnetic system, viewed parallel to an X-direction (Y in Figure 26) extending perpendicularly to the optical axis, is arranged in its entirety next to and outside the coil system, the magnetic system comprises a first part (2-22) and a second part (2-24) on opposite sides of the optical axis, the first part and the second part of the magnetic system each comprise at least a first and a second permanent magnet (see magnets labeled S→N and N←S), at least a part of the coil system being situated in a magnetic stray field of the magnetic system (see also Figure 32); and the coil system further comprises a portion of the coil system (2-16) situated symmetrically with respect to a junction of the first and the second magnet for both the first and second part of the magnetic system, said portion being situated between a pair of portions of the coil system (2-

Art Unit: 2652

18 & 2-20) arranged directly opposite, respectively, the first and second parts of the magnetic system such that the first and second part of the magnetic system extend entirely across the pair of portions of the coil system.

In regard to claim 2, Schell et al. disclose that the magnetic system comprises the first part (2-22) and the second part (2-24) which are each arranged, in their entirety, next to and outside the coil system near, respectively, a first side of the lens system and a second side of the lens system which, viewed in a direction parallel to the X-direction (Y in Figure 26), is opposite the first side, the pair of portions of the coil system having a first part (2-18) of the coil system arranged near the first side, and a second part (2-20) of the coil system arranged near the second side, being situated, at least partly, in a magnetic stray field (see also Figure 32) of, respectively, the first part and the second part of the magnetic system.

In regard to claim 3, Schell et al. disclose that the first part and the second part of the magnetic system, and the first part and the second part of the coil system, viewed in a direction parallel to the X-direction, are symmetrically arranged (as shown in Figure 26) with respect to the optical axis.

In regard to claim 4, Schell et al. disclose that the first and the second permanent magnet (Figure 26, magnets labeled S→N and N←S) which, viewed in a direction parallel to the optical axis are arranged next to each other and have a direction of magnetization extending, respectively, parallel to the X-direction and parallel to an X'-direction opposite to the X-direction, while the first part and the second part of the coil system each comprise at least an electric coil having a first part and a second part, which are provided with wire portions extending perpendicularly to the X-direction and perpendicularly to the optical axis, said first

and said second part of the coil of the first part of the coil system, viewed in a direction parallel to the X-direction, being arranged directly opposite, respectively, the first and the second magnet of the first part of the magnetic system, and said first and said second part of the coil of the second part of the coil system, viewed in a direction parallel to the X-direction, being arranged directly opposite, respectively, the first and the second magnet of the second part of the magnetic system.

In regard to claim 5, Schell et al. disclose that the first and the second permanent magnets (Figure 26, magnets labeled S→N and N←S) which, viewed in a direction parallel to the optical axis, are arranged next to each other and have a direction of magnetization extending, respectively, parallel to the X-direction and parallel to an X'- direction opposite to said X-direction, while the coil system comprises at least one electric coil having a first part and a second part, which are provided with wire portions extending perpendicularly to the X-direction and perpendicularly to the optical axis, said first part and said second part of the coil being arranged, viewed in a direction parallel to the X-direction, directly opposite, respectively, one of the two magnets of the first part of the magnetic system and one of the two magnets of the second part of the magnetic system.

In regard to claim 6, Schell et al. disclose that the X-direction (Y in Figure 26) extends transversely to an information track present on the information layer, and in that the first and the second permanent magnets which, viewed parallel to the optical axis, are arranged next to each other and have a direction of magnetization extending, respectively, parallel to the X-direction and parallel to the X'-direction opposite to the X-direction, while the coil system comprises an electric coil having a first part and a second part, which are provided with wire portions

extending perpendicularly to the X-direction and perpendicularly to the optical axis, said parts of the coil being arranged, viewed in a direction parallel to the optical axis, in a transition region of the two magnets (see also Figure 32) of, respectively, the first part and the second part of the magnetic system.

In regard to claim 7, Schell et al. disclose that the X-direction (Y in Figure 26) extends at least substantially parallel to an information track present on the information layer, and in that the first part and the second part of the coil system each comprise at least one further electric coil from said portion having a first part and a second part, which are provided with wire portions extending parallel to the optical axis, the first part and the second part of the further coil of the first part of the coil system, viewed in a direction parallel to the X-direction, being arranged directly opposite, respectively, the first magnet and a magnetizable part (Figure 28, element 2-80) of the first part of the magnetic system, which magnetizable part, viewed perpendicularly to the optical axis and perpendicularly to the X-direction, is situated next to the first magnet, and the first part and the second part of the further coil of the second part of the coil system, viewed in a direction parallel to the X-direction, being arranged directly opposite, respectively, the first magnet and a magnetizable part of the second part of the magnetic system, which magnetizable part, viewed perpendicularly to the optical axis and perpendicularly to the X-direction, is situated next to the first magnet.

In regard to claim 8, Schell et al. discloses an optical player comprising an optical scanning device (Figure 26, see claim 1 above for similar limitations) for scanning an information layer of an optically scannable information carrier, and a table (inherent: necessary part for placing the carrier) which can be rotated about an axis of rotation, on which table the

Page 7

Art Unit: 2652

information carrier can be placed, said scanning device being provided with a radiation source, an optical lens system with an optical axis for focusing a radiation beam supplied, in operation, by the radiation source into a scanning spot on the information layer, and an actuator by means of which the lens system can be displaced with respect to a stationary part of the scanning device, at least in a direction parallel to the optical axis, and a displacement device (Figure 28, element 2-82) by which at least the lens system of the scanning device can be displaced, with respect to the axis of rotation, mainly in a radial direction.

In regard to claim 9, Schell et al. disclose an optical scanning device (Figure 26) having a radiation source providing a radiation beam, an optical lens system with an optical axis for focusing the radiation beam into a scanning spot on an information layer, and an actuator that can displace the lens system, the actuator being provided with an electric coil system (2-16, 2-18 & 2-20), which is arranged in a fixed position with respect to the lens system, and a magnetic system (2-22 & 2-24) which is arranged in a fixed position with respect to a stationary part, comprising: a first part (2-22) and a second part (2-24) to the magnetic system arranged on opposite sides of the optical axis, the first part and the second part of the magnetic system each comprise at least a first and a second permanent magnet (see magnets labeled  $S \rightarrow N$  and  $N \leftarrow S$ ). at least a part of the coil system being situated in a magnetic stray field of the magnetic system (see also Figure 28), a portion of the coil system situated symmetrically with respect to a junction of the first and the second magnet for both the first and second part of the magnetic system, said portion being situated between a pair of portions of the coil system arranged directly opposite, respectively, the first and second part of the magnetic system such that the first and second part of the magnetic system extend entirely across the pair of portions having wires

extending perpendicular to the optical path; and the magnetic system, viewed parallel to an X-direction extending perpendicularly to the optical axis, is arranged is arranged in its entirety next to and outside the coil system.

In regard to claim 10, Schell et al. disclose the first part (2-22) and the second part (2-24) to the magnetic system which are each arranged next to and outside the coil system near a first side of the lens system and a second side of the lens system which is opposite the first side of the lens system; the pair of portions of the coil system having a first part (2-18) and a second part (2-20), the first part of the coil system arranged near the first side, and the second part of the coil system arranged near the second side.

In regard to claim 11, Schell et al. disclose that the first part and the second part of the magnetic system, and the first part and the second part of the coil system are symmetrically arranged (as shown in Figure 26) with respect to the optical axis.

In regard to claim 12, Schell et al. disclose that the first part and the second part of the magnetic system each comprise the first and the second permanent magnet (Figure 26, magnets labeled S→N and N←S) having respective directions of magnetization extending parallel to the X-direction and parallel to an X'-direction opposite to the X-direction, while the first part and the second part of the coil system each comprise at least an electric coil having a first part and a second part, which are provided with wire portions extending perpendicularly to the X-direction and perpendicularly to the optical axis, said first and said second part of the coil of the first part of the coil system, viewed in a direction parallel to the X-direction, being arranged directly opposite, respectively, the first and the second magnet of the first part of the magnetic system, and said first and said second part of the coil system, viewed in a

. Art Unit: 2652

direction parallel to the X-direction, being arranged directly opposite, respectively, the first and the second magnet of the second part of the magnetic system.

In regard to claim 13, Schell et al. disclose that the first part and the second part of the magnetic system each further comprise the two permanent magnets (Figure 26, magnets labeled S > N and N < S) which, viewed in a direction parallel to the optical axis, are arranged next to each other and have a respective direction of magnetization parallel to the X-direction and parallel to an X'- direction opposite to said X-direction, while the coil system comprises at least one electric coil having a first part and a second part, which are provided with wire portions extending perpendicularly to the X-direction and perpendicularly to the optical axis, said first part and said second part of the coil being arranged, viewed in a direction parallel to the X-direction, directly opposite, respectively, one of the two magnets of the first part of the magnetic system and one of the two magnets of the second part of the magnetic system.

In regard to claim 14, Schell et al. disclose that the X-direction (Y in Figure 26) extends at least substantially parallel to an information track present on the information layer, and in that the first part and the second part of the coil system each comprise at least one further electric coil from said portion having a first part and a second part, which are provided with wire portions extending parallel to the optical axis, the first part and the second part of the further coil of the first part of the coil system being arranged directly opposite, respectively, the first magnet and a magnetizable part (Figure 28, element 2-80) of the first part of the magnetic system, which magnetizable part, viewed perpendicularly to the optical axis and perpendicularly to the X-direction, is situated next to the first magnet, and the first part and the second part of the further coil of the second part of the coil system, viewed in a direction parallel to the X-direction,

Art Unit: 2652

being arranged directly opposite, respectively, the first magnet and a magnetizable part of the second part of the magnetic system, which magnetizable part, viewed perpendicularly to the optical axis and perpendicularly to the X-direction, is situated next to the first magnet.

In regard to claim 15, Schell et al. disclose an optical player comprising an optical scanning device (Figure 26, see claim 1 above for similar limitations) for scanning an information layer of an optically scannable information carrier, and a table (inherent: necessary part for placing the carrier), which can be rotated about as axis of rotation, on which table the information carrier can be placed, said scanning device being provided with a radiation source, an optical lens system (2-12) with an optical axis for focusing a radiation beam supplied, in operation, by the radiation source into a scanning spot on the information layer, and an actuator by means of which the lens system can be displaced with respect to a stationary part of the scanning device, at least in a direction parallel to the optical axis, and a displacement device (Figure 28, element 2-82) by means of which at least the lens system of the scanning device can be displaced, with respect to the axis of rotation, mainly in a radial direction.

In regard to claim 16, Schell discloses an optical scanning device (Figure 26) having a radiation source providing a radiation beam, an optical lens system (2-12) with an optical axis for focusing the radiation beam into a scanning spot on an information layer, and an actuator (Figure 26) that can displace the lens system, the actuator being provided with an electric coil system (2-16, 2-18 & 2-20), which is arranged in a fixed position with respect to the lens system, and a magnetic system (2-22 & 2-24) which is arranged in a fixed position with respect to a stationary part, comprising: a first part (2-22) and a second part (2-24) to the magnetic system arranged on opposite sides of the optical axis, the first part and the second part of the magnetic system each

comprise at least a first and a second permanent magnet (see magnets labeled  $S \rightarrow N$  and  $N \leftarrow S$ ), at least a part of the coil system being situated in a magnetic stray field of the magnetic system (see Figure 32); a portion (2-16) of the coil system situated symmetrically with respect to a junction of the first and the second magnet for both the first and second part of the magnetic system, said portion being situated between a pair of portions (2-18 & 2-20) of the coil system, said pair of portions being in a symmetrical arrangement in an area between the first and second part of the magnetic system such that the first and second part of the magnetic system extend entirely across the pair of portions in a plane parallel the optical axis; and the magnetic system, viewed parallel to an X-direction (Y in Figure 26) extending perpendicularly to the optical axis, is arranged in its entirety next to and outside the coil system.

In regard to claim 17, Schell et al. disclose that the pair of portions of the coil system contains wires extending perpendicular to the optical axis (for example, 2-58 in Figure 27).

In regard to claim 18, Schell et al. disclose that the pair of portions of the coil system contains wires extending parallel to the optical axis (for example, 2-56 in Figure 27).

In regard to claim 19, Schell et al. disclose the first part (2-22) and the second part (2-24) to the magnetic system which are each arranged next to and outside the coil system near a first side of the lens system and a second side of the lens system which is opposite the first side of the lens system; the pair of portions of the coil system having a first part (2-18) and a second part (2-20), the first part of the coil system arranged near the first side, and the second part of the coil system arranged near the second side.

Art Unit: 2652

In regard to claim 20, Schell et al. disclose that the first part and the second part of the magnetic system, and the first part and the second part of the coil system are symmetrically arranged with respect to the optical axis (as shown in Figure 26).

#### Response to Arguments

- 6. Applicant's arguments filed March 4, 2005 have been fully considered but they are not persuasive.
  - a. The Applicant argues on page 12, first and third paragraphs that claims 1 & 9 are not anticipated by Schell et al. because "the magnetic system of Schell et al. does not extend entirely across the pair of portions of the coil system...[and] only extends partially across the pair of portions of the coil system". The Examiner disagrees. The recitation in claims 1 & 9 that "the first and second part of the magnetic system extend entirely across the pair of portions of the coil system" is broad and has been interpreted by the Examiner as being anticipated by Figure 26 of Schell et al. For example, elements 2-22 & 2-24 extend entirely in the Y direction across the pair of portions of element 2-20.

#### Conclusion

7. THIS ACTION IS MADE FINAL. Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37

Art Unit: 2652

CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event,

however, will the statutory period for reply expire later than SIX MONTHS from the mailing

Page 13

date of this final action.

8. Any inquiry concerning this communication or earlier communications from the

examiner should be directed to Peter Vincent Agustin whose telephone number is 571-272-7567.

The examiner can normally be reached on Monday-Friday 9:30-5:30 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Hoa Thi Nguyen can be reached on 571-272-7579. The fax phone number for the

organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published applications

may be obtained from either Private PAIR or Public PAIR. Status information for unpublished

applications is available through Private PAIR only. For more information about the PAIR

system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR

system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Peter Vincent Agustin

Art Unit 2652

BRIAN E. MILLER

PRIMARY EXAMINER